

## V5 Classic Series **C Series**

### LEGEND RETOLD

The Classic Series delivers intuitive interactions as well as outstanding sound and video performance. For both local meetings and teleconferences, participants may visualise their ideas instantly via updated audio & visual systems, giving the distant meeting attendees the feeling as if they were joining the session in person.



#### 4k UHD Display

Low Parallax | Anti-glare  
90% NTSC Wide color Gamut

#### Seam Speakers

2.1 Stereo Sound  
40W High-Power Speaker

#### 12MP HDR Camera

Auto Framing  
Higher SNR

#### Multiple Sizes

55/65/75/86 Inches  
Available

#### Smart Writing

High-precision  
IR Touch Technology

#### 3 Display Modes

Presentation | Standard  
Night Mode



USB Type-C  
Bridging the Divide



Multi-screen  
Interaction  
(up to 4 devices)



Optional  
Android 9.0/Windows 10



Auto Zoom In  
On the Speaker



6-element  
Microphone Array



Up to 8 metres  
Voice Pickup

Specification	C55FA	C65FA	C75FA	C86FA
<b>Display</b>				
Size	55 inch	65 inch	75 inch	86 inch
Ratio	16:9	16:9	16:9	16:9
Resolution	3840×2160	3840×2160	3840×2160	3840×2160
Contrast Ratio	4500:1	4000:1	4000:1	4000:1
Viewing Angle	178° (H/V)	178° (H/V)	178° (H/V)	178° (H/V)
Colour Gamut	90% NTSC	90% NTSC	90% NTSC	90% NTSC
Backlight Structure	DLED	DLED	DLED	DLED
Lifespan	≥30,000 hours	≥30,000 hours	≥30,000 hours	≥30,000 hours
<b>Touch System</b>				
Touch Principle	Infrared	Infrared	Infrared	Infrared
Touch Points	20 Points	20 Points	20 Points	20 Points
Supported Systems	Windows 10/Windows 8/ Windows 7/Windows XP/ Android/Linux/macOS X/Chrome			
Minimum Recognisable Object	2mm	2mm	2mm	2mm
Touch Object	Finger, Stylus	Finger, Stylus	Finger, Stylus	Finger, Stylus
Touch Accuracy	±1mm	±1mm	±1mm	±1mm
Writing Height	≤2mm	≤2mm	≤2mm	≤2mm
Touch Resolution	32768(W)×32768(D)	32768(W)×32768(D)	32768(W)×32768(D)	32768(W)×32768(D)
<b>Speakers</b>				
Channel	2.1	2.1	2.1	2.1
Power	2×10W+20W	2×10W+20W	2×10W+20W	2×10W+20W
<b>Microphone</b>				
Quantity	6	6	6	6
Voice Pickup Range	Up to 8m	Up to 8m	Up to 8m	Up to 8m
<b>Camera</b>				
Quantity	1	1	1	1
Pixels	12MP	12MP	12MP	12MP
Location	In the Middle of the Upper Bezel			
<b>I/O Ports</b>				
HDMI IN	1	1	1	1
USB 2.0	1	1	1	1
USB 3.0	2	2	2	2
USB Type-C	2	2	2	2
TOUCH	1	1	1	1
AUDIO OUT	1	1	1	1
RS232	1	1	1	1
<b>Compatible Modules*</b>				
PC Module	MT51 (Windows 10)	MT51 (Windows 10)	MT51 (Windows 10)	MT51 (Windows 10)
Android Module	SA08 (Android 9.0)	SA08 (Android 9.0)	SA08 (Android 9.0)	SA08 (Android 9.0)
<b>Accessories</b>				
Power Cable	×1	×1	×1	×1
Stylus	×2	×2	×2	×2
Wall Mount	×1	×1	×1	×1
Wi-Fi Module	×1	×1	×1	×1
<b>Environment</b>				
Operation Temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C
Operation Humidity	10% to 90%RH	10% to 90%RH	10% to 90%RH	10% to 90%RH
Storage Temperature	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C	-20°C to 60°C
Storage Humidity	10% to 90%RH	10% to 90%RH	10% to 90%RH	10% to 90%RH
Altitude	≤5000 metres	≤5000 metres	≤5000 metres	≤5000 metres

**Corporate Office:** Shiyuan India Private Limited  
306-307, Third Floor, Elegance Tower Jasola, District Centre,  
New Jasola, South East Delhi, Delhi, 110025  
**Tel:** +91 - 81910 72668 | **Customer Care No.:** 1800 120 122 045  
**www.maxhub.in** | **E-mail:** maxhubindia@cvte.com

**MAXHUB**

© Copyright 2021 Shiyuan India Private Limited. All right reserved. Corporate names and trademarks are property of their perspective companies. Features & Specification may change without any prior notice