

# MAXHUB Wireless Screen Sharing Dongle WT15

Instant Collaboration, Zero Hassle



## Share Your Screen in Stunning 4K

Crystal-clear 4K presentations, ultra-low latency for smooth, responsive, synced screen sharing.



## Plug and Play in 3 Seconds\*

Simply plug the dongle into your laptop and start sharing within 3 seconds.



## 1080P Wireless BYOD\*, Elevated

Wirelessly connect personal devices to room cameras, mics and speakers.

1080P BYOD hardware decoding boosts transmission bitrate by 50% for stable, pro-grade conferencing.



## Enterprise-Grade Security

AES 128-bit multi-layered encryption, dynamic key negotiation and multi-factor authentication for independent connection security.

\*3 Seconds: Response time from dongle insertion to laptop screen projection readiness; USB-C:  $\geq 3s$ , USB-A:  $\geq 10s$ .

\*BYOD: BYOD functionality is exclusive to the WT15M model.

# Built for the Modern Workplace

Instant Collaboration, Zero Hassle



## 1 Durable Cable and Adapter

- Over 20,000 bending tests for extended lifespan.
- Integrated USB adapter for seamless USB-C/USB-A switching.

## 2 Anti-Loss Design

Dedicated lanyard hole for secure mounting, effectively preventing misplacement

## Wireless Screen Sharing Dongle

Interface		
USB Type-C		×1
USB Type-A (Adapter)		×1

  

Performance		
Wireless Connection Range (Max.)		12 m / 39 ft
Supported Operating Systems		Windows 7/10/11, macOS 10.12 or later
Startup Time		≥ 3s (USB-C), ≥ 10s (USB-A)
Disconnect Time		≥ 5s
Transmission Latency (1080P)		≥ 90 ms
Wireless Screen Sharing Resolution (Max.)		3840×2160@30 Hz
Wireless BYOD Resolution (Max.)		1920×1080@30 Hz Only WT15M supports BYOD
Touchback Control		Supported

  

Indicator Light		
Connecting to Endpoint	Flash White	The dongle is starting up
	Flash Blue	Pairing/Updating
	Solid Blue	Paired successfully
	Solid Red	Failed to pair
Connecting to Laptop	Flash White	Pairing
	Solid White	Paired successfully
	Solid Green	Sharing the screen

  

Wi-Fi	
Wi-Fi Standard	802.11a/n/ac
Wi-Fi Frequency	5G Hz

  

Power	
Power Supply	5 V@500 mA
Power Consumption	≤2.5 W

  

Physical Specification	
Dimension (L×H×D)	182.5×15.4×76.1 mm
Shipping Dimension (L×H×D)	1pcs: 196×28×110 mm 60pcs: 420×350×360 mm
Net Weight	73 g
Gross Weight	1pcs: 230 g 60pcs: 15.4 kg

  

Environment	
Operating Temperature	0°C~40°C
Storage Temperature	-20°C~60°C
Operating Humidity	10%~90%RH
Storage Humidity	10%~90%RH
Altitude	Below 5000 meters

### Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may be subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.